Spare Tire Display Support

Completely Wireless Transmission

Multicolor Display

Pressure & Temperature Alternating Display

5 to 7 Year Battery

24 Hour Monitoring

Automatic Brightness

Battery Voltage Monitoring

L-LW10-2
(Ten+One tires)

L-LW6-2
(Six+One tires)

L-LW8-2
(Eight+One tires)

Suitable For Truck & Bus

Transmitter Specifications

Battery Life	About 5 to 7 years
Battery Voltage	3.0 V Lithium Battery
Temperature Ranges:	
Storage	-40° C to 125° C
Operating	-40° C to 115° C
Transmitting Power	Max. 5dBm
Transmitting Frequency	433.92 MHZ
Pressure Monitoring Range	0 ~ 188 psi 0 ~ 13 bar
Pressure Reading Accuracy	± 3 psi (± 0.2 bar)
Temperature Monitoring Range	-40° C to 115° C
Temperature Reading Accuracy	± 3° C
Module Weight	29.2 g ± 1 g
Size	60x34x19 (mm)

Receiver Specifications

Power Supply	DC 9V ~36 V
Operating Current	<100mA
Storage Temperature	-40° C to 90° C
Operating Temperature	-30° C to 85° C
Pressure Display Range	0 ~ 188 psi 0 ~ 13 bar
Temperature Display Range	-40° C to 115° C
Size	85x55x17 (mm)

L-LW6-1(Six tires)



L-LW8-1(Eight tires)



L-LW10-1(Ten tires)